

## HT6/90/30 TOP SECTION OF 2-PIECE DEER FENCE

### Overview

Due to difficult access it is not always possible to install a 'one-piece' deer fence. In such areas it is common practice to build the fence using two nets. The bottom section can be either rabbit net or stock fencing. HT6/90/30 offers a slightly taller net; the reduced number of line wires combined with the increase in vertical wire spacings creates a manageable top section to your 2-piece deer fence. HT6/90/30 is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

### Compliance with British and European Standards

BSEN 10218 - Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.

BSEN 10223 - Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.

BSEN 10244 - Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).

### Sustainability

All Tornado products are 100% recyclable.

### Traceability

This fence is batch marked and can be traced back to point of manufacture.

### Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating.

### Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

### Suitable for

- Deer Exclusion

### Specification

No. of Line Wires	6
Overall Height (cm)	90
Distance between stay wires (cm)	30
Top & bottom line wire specification	2.5mm dia - 1235-1390 N/mm <sup>2</sup>
Intermediate line wire specification	2.5mm dia - 1235-1390 N/mm <sup>2</sup>
Vertical stay wire specification	2.5mm dia - 695-850 N/mm <sup>2</sup>
Average Weight per 100 Metre Roll (kg)	37.31
Material Composition	Heavily galvanised steel wire


### Product Codes

HZST069002	100 metre roll
HZST069004	250 metre roll

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

## Fence Layout Detail



- Top wire 2.5mm high tensile
- Intermediate line wire 2.5mm high tensile
- Vertical stay wire 2.5mm



## Line Wire Detail

		230mm
		200mm
		180mm
		152mm
		140mm
300mm	300mm	

## Fence Configuration Detail



### Hinge Joint

Traditional cost effective joint. Enables the netting to be turned out or cranked for use in special applications.

### Related Products

- Barbed wire
- Plain wire
- Staples
- Stock-ade staple gun
- Range of fence installation tools