

Overview

R15/158/5 comes with pre-stripped ends for ease of joining. It is ideal for use along highways or areas where badger movements need to be restricted. The solid, closely spaced vertical stay wires add strength and help prevent badgers from pushing through the fence. R15/158/5 exceeds Highways Agency specifications H46 and H47; it can also be used as embankment netting. Manufactured with high tensile wire, it strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

Compliance with British and European Standards

BSEN 10218 - Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.

BSEN 10223 - Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.

BSEN 10244 - Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approximately 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. The bottom 600mm can be buried and turned out to prevent badgers digging below the fence, and barbed wire can be added to the top of the fence to prevent climbing when used as a stand-alone badger fence.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

- Badger Exclusion

Specification

No. of Line Wires	15
Overall Height (cm)	158
Distance between stay wires (cm)	5
Top & bottom line wire specification	2.5mm dia - 1235-1390 N/mm ²
Intermediate line wire specification	2.5mm dia - 1235-1390 N/mm ²
Vertical stay wire specification	2.5mm dia - 695-850 N/mm ²
Average Weight per 50 Metre Roll (kg)	109.15
Material Composition	Heavily galvanised steel wire

Product Codes

RZST151501	50 metre roll
------------	---------------

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

