

Overview

Tornado's Titan 949-6 12.5g is a high tensile fence; its height of 49" and its solid vertical wires for increased net strength make it ideally suited for containing hogs or cattle.

The Titan fixed knot is extremely strong and durable and helps to create a highly visible barrier. If hogs are being fenced in, a line of barbed wire below the net is recommended. This fence provides an additional line wire and an extra 7" in height to the 842-6 specification, making it an ideal solution where a taller net is required.

Tornado Titan Fence is manufactured with high tensile wire which strains tighter than low carbon steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering, avoiding the need to annually re-tighten the fence.

Compliance with North American Standards

- Class 3 zinc galvanized coating meets or ASTM A641

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approximately 50%. Avoid driving staples tight against the wire as this will damage the galvanized coating. Two lines of plain can be added to the top of the fence if required to provide additional height. Where cattle are being contained, two lines of barbed wire can be used to prevent downward pressure being exerted directly onto the net. A line of barbed wire below the net can help to deter hogs and other animals from digging underneath it.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for


- Hogs
- Cattle

Specification

| | |
|--|---------------------------------------|
| No. of horizontal line wires | 9 |
| Overall height (inches) | 49 |
| Distance between vertical wires (inches) | 6 |
| Top & bottom line wire specification | 12.5g - 179 - 201 ksi |
| Intermediate line wire specification | 12.5g - 179 - 201 ksi |
| Vertical stay wire specification | 12.5g - 100 - 123 ksi |
| Average weight per 330 ft roll (lbs) | 187 |
| Material composition | Class 3 heavily galvanized steel wire |


All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

Top wire 12.5g high tensile
 Intermediate line wire 12.5g high tensile
 Vertical stay wire 12.5g




Fence Layout Detail

Line Wire Detail




Fence Configuration Detail



Information on ancillary items and tools can be found on the relevant data sheets.

Titan Fixed Knot

The Tornado Titan joint is a non-slip fixed knot incorporating a continual vertical stay wire. It has exceptional impact resistance making it ideal for high pressure applications.



Related Products

- Barbed wire
- Plain wire
- Staples
- Range of fence installation tools